



64-70 MUSTANG MEGA BRIGHT L.E.D. COURTESY LIGHTS



@AUTOWORKSPARTS




@MUSTANGS_AND_AUTOWORKS

@AUTOWORKSRESTOMOD

THIS KIT CONTAINS:

- (2) L.E.D. Bright White Lamps (4 for double lamp kits)
- (2) Mounting Screws
- (2) Retainer Clips
- (2) Mega Bright Lamp Brackets

WWW.AUTOWORKSPARTS.com



Here's what you'll need:

- ☐ 1..... Philips screwdriver
- ☐ 2..... 3/8" Wrench
- ☐ 3..... Wire cutters
- ☐ 4..... Wire crimpers
- ☐ 5..... Any safety equipment you deem necessary such as gloves and goggles.

NOTE: These recommendations are based on cars with original hardware and wiring. Due to the nature of older vehicles, your hardware and wiring may have been modified over time and may no longer have original hardware or wiring. Please adjust accordingly.

PHASE 1: REMOVING THE OE COURTESY LAMP

1. Disconnect the battery.
2. Locate the underdash courtesy light bracket. There should be one bracket on the driver's side, and one bracket on the passenger side.
3. With your Philips screw driver, remove the screw that holds the courtesy bracket to the dash. Your 3/8" Wrench may be necessary here. There is a nut on the top side of the bracket. If the screw is spinning and not removing, then hold the nut with your 3/8" Wrench and continue removing the screw.
4. Using your wire cutters, cut the single black wire to your original courtesy light.

PHASE 2: INSTALLING THE MEGA BRIGHT COURTESY LAMP

1. Using your wire cutters, cut back the sheath on the original black wire your courtesy lamp was connected to.
2. Remove the red female wire terminal from your new Mega Bright L.E.D. Courtesy Lamp. You're going to connect this end to the wire you just cut.
3. With your wire crimpers, crimp the red female terminal to the black wire. Make sure the terminal is firmly secured to the wire.
4. Unscrew the single screw and clip attached to the Mega Bright lamp bracket.

*****IMPORTANT** Be sure that you do NOT remove the ground wire connected to the clip.***

5. Line the clip up with the original hole on your dash.
6. Line the Mega Bright bracket hole to the hole on the dash and the clip.

*****NOTE** The components should be layered as follows (from bottom to top): Mega Bright Bracket > Dash > Clip w/Ground Wire***

7. Attach the screw through the bracket, dash and clip. Fasten securely.
8. Plug the male terminal on the courtesy lamp into the red female terminal

Tech Support: 619-569-1574